

**Amendments to the Claims:**

This listing of claims will replace all prior versions and listing of claims in the application:

**Listing of Claims:**

- 5      Claim 1 (currently amended): A pixel structure of an active matrix display device, the active matrix display device having a source of first potential and a source of second potential, the pixel structure comprising:
- 10                      a plurality of active-type light emitting devices connected in parallel with each other, each of the active-type light emitting devices being electrically connected between the source of first potential and the source of second potential;
- 15                      a single first active device having a first end electrically connected to a scanning line, a second end electrically connected to a data line, and a third end electrically connected to a switching end of each of the active-type light emitting devices for switching each ~~all~~ of the active-type light emitting devices ~~simultaneously~~; and
- 20                      a storage capacitor having a first electrode electrically connected to the third end of the first active device and the switching end of the active-type light emitting devices, and a second electrode electrically connected to the source of first potential end.
- 25      Claim 2 (currently amended): The pixel structure of claim 1, wherein the single first active device is a first thin film transistor, and the first end is a gate electrode of the first thin film transistor, the second end is a drain electrode of the first thin film transistor, and the third end is a source electrode of the first thin film transistor.
- 30      Claim 3 (currently amended): The pixel structure of claim 1, wherein the storage capacitor is electrically connected between the third end of the single first active device and the source of first potential.

Claim 4 (previously presented): The pixel structure of claim 3, wherein the source of first potential is utilized for supplying a constant potential.

5    Claim 5 (currently amended): The pixel structure of claim 1, wherein each of the active-type light emitting devices comprises:

          a second active device having a fourth end electrically connected to the third end of the single first active device, a fifth end connected to the source of first potential, and a sixth end, wherein the fourth end is  
10           the switching end; and

          a light emitting device having a seventh end connected to the sixth end and an eighth end connected to the source of second potential.

15    Claim 6 (previously presented): The pixel structure of claim 5, wherein when an electrical shortage occurs in one of the active-type light emitting devices, the pixel structure displays an image via the other active-type light emitting devices.

20    Claim 7 (original): The pixel structure of claim 5, wherein each of the second active devices comprises a second thin film transistor or a complementary metal-oxide semiconductor (CMOS).

25    Claim 8 (original): The pixel structure of claim 7, wherein the fourth end is a gate electrode of the second thin film transistor, the fifth end is a source electrode of the second thin film transistor, and the sixth end is a drain electrode of the second thin film transistor.

30    Claim 9 (original): The pixel structure of claim 5, wherein each of the light emitting devices comprises an organic light emitting diode (OLED) or a light emitting diode (LED).

Claim 10 (original): The pixel structure of claim 9, wherein the seventh end is an anode of the light emitting device, and the eighth end serves as a cathode of the light emitting device.

5

Claim 11 (currently amended): An active matrix display device comprising:

a plurality of scanning lines;

a plurality of data lines;

10 a plurality of pixels, each of the pixels electrically connected to one corresponding scanning line and one corresponding data line, each of the pixels comprising:

a single first active device having a first end electrically connected to the corresponding scanning line, a second end electrically connected to the corresponding data line, and a third end;

15 a plurality of active-type light emitting devices electrically connected in parallel with each other, each of the active-type light emitting devices being connected between a source of first potential and a source of second potential, each of the active-type light emitting devices comprising:

20 a light emitting device electrically connected to the source of second potential; and

a second active device having a fourth end electrically connected to the third end, a fifth end electrically connected to the source of first potential, and a sixth end electrically connected to the light emitting device, wherein the single first active device switches each of the active-type light emitting devices  
~~wherein the first active device switches all of the active-type light emitting devices simultaneously;~~ and

25 a storage capacitor having a first electrode electrically connected to the third end of the single first active device and the fourth end of the

30

active-type light emitting devices, and a second electrode electrically connected to the source of first potential end.

5 Claim 12 (currently amended): The active matrix display device of claim 11, wherein the single first active device is a first thin film transistor, and the first end is a gate electrode of the first thin film transistor, the second end is a drain electrode of the first thin film transistor, and the third end is a source electrode of the first thin film transistor.

10 Claim 13 (currently amended): The active matrix display device of claim 11, wherein the storage capacitor is electrically connected between the third end of the single first active device and the source of first potential that is utilized for supplying a constant potential.

15 Claim 14 (previously presented): The active matrix display device of claim 13, wherein the source of first potential is utilized for supplying a constant potential.

20 Claim 15 (original): The active matrix display device of claim 11, wherein each of the second active devices comprises a second thin film transistor or a complementary metal-oxide semiconductor (CMOS).

25 Claim 16 (original): The active matrix display device of claim 15, wherein the fourth end is a gate electrode of the second thin film transistor, the fifth end is a source electrode of the second thin film transistor, and the sixth end is a drain electrode of the second thin film transistor.

30 Claim 17 (original): The active matrix display device of claim 11, wherein each of the light emitting devices comprises an organic light emitting diode (OLED) or a light emitting diode (LED).

5      Claim 18 (previously presented): The active matrix display device of claim 11,  
         wherein when an electrical shortage occurs in one of the active-type light  
         emitting devices of a pixel, the pixel displays an image via the other  
         active-type light emitting devices of the pixel.